



Technical Data Sheet

ONE Outdoor Speaker Cable


152m

Makes installation easier

The Kordz ONE Series Outdoor Speaker Cable is purpose-built for professional AV integrators seeking long-lasting, high quality audio connectivity in outdoor environments. With 99.99% Oxygen Free Copper (OFC) conductors, the cable delivers outstanding signal integrity with minimal resistance, ensuring clear, powerful sound even over extended cable runs. Each strand is polished to reduce oxidation, maintaining conductivity and performance for years to come. The UV-stabilised polyethylene jacket is engineered to withstand prolonged exposure to sunlight, harsh weather and temperature extremes without degrading or becoming brittle. Balanced strand counts provide the optimal blend of power handling and flexibility, making installation straightforward.

Practical installer-focused features include metre-marked lengths for precise pulls, an internal nylon ripcord for quick, clean stripping, and durable reel-box packaging for easy handling on-site. Designed to meet

- UV-stabilised polyethylene jacket engineered for long-term outdoor use
- 99.99% Oxygen Free Copper conductors for high quality audio performance
- Balanced strand count for flexibility and ease of installation
- Polished conductor surface reduces oxidation for long lasting reliability
- Industry-standard internal colour coding for straightforward termination
- Metre-marked with internal nylon ripcord for quick, precise stripping
- Durable reel-box packaging simplifies transport and deployment
- Compliant with AS/NZS S008:2010 and RoHS standards
- Backed by Kordz 5-Year Warranty for peace of mind



Specifications						ONE-SP142		ONE-SP144	
Conductors	AWG (Gauge)					14		14	
	# of Cores					2		4	
	# of Strands					82		82	
	Area(mm²)					2.083		2.083	
	Strand Diameter (mm)					0.18 ± 0.008			
	Material					Oxygen Free Copper (OFC)			
Insulation	Material Rating					Polyvinyl Chloride (PVC)			
	Outer Diameter (mm)					3.00 ± 0.15			
	Average Thickness (mm)					0.50			
	Material					Nylon			
Jacket	Material Rating					Polyethylene (PE)			
	Outer Diameter (mm)					7.50 ± 0.20		8.80 ± 0.20	
	Average Thickness (mm)					0.65			
	Insulation Resistance (10m at 20°C)					Minimum 100MQ (Mega Ohms)			
Conductor Resistance (Ohms/km at 20°C)					Max. 14.68Ω/km				
Dielectric Strength					500V AC/1min				
Environment Compliance					RoHS, REACH				
Mechanical									
Minimum Bend Radius	without load					≥ 30.0mm		≥ 35.2mm	
	with load					≥ 60.0mm		≥ 70.4mm	
Temperature Range	During operation					-20 °C to 60°C			
	During installation					0°C to 50°C			
Model	Part No	Colour	Material	Fire Rating	Spool Length	Pallet	Packaging Style	Packaging Dimensions	
ONE-SP142 OD	K11803-152M-BK	Black	PE	N/A	152.5m / 500ft (metre-marked)	36 boxes per pallet	Reel Box	330mm x 260mm x 345mm 12.99in × 10.24in × 13.58in	
ONE-SP144 OD	K11903-152M-BK								

Kordz products are sold with a limited warranty as outlined at: www.kordz.com
 ©2025 Kordz International. All rights reserved. Kordz Connectivity.Assured & Kordz range logos are trademarks or registered trademarks of Kordz International in Hong Kong and in other countries.
 All other trademarks are the property of their respective owners.