



Technical Data Sheet

○N∈² 18Gbps Passive HDMI Cable









The Kordz ONEv2 HDMI Cable is the professional grade passive HDMI cable designed to provide reliable, economical, uncompressed 4K connectivity for high volume commercial integration projects. It delivers full 18Gbps performance at every length up to 5m. Its slim, flexible, fire-rated PVC jacket and compact connector ensure durability, easy routing $and \ secure \ connections, even in tight \ spaces. \ Supplied in eco-friendly \ recyclable \ paper \ packaging, the \ ONEv2 \ HDMI$ Cable is quick to open, easy to clean up, and comes backed by the Kordz lifetime warranty for peace of mind.

- Full 18Gbps bandwidth for reliable uncompressed 4K signal at all lengths up to 5m
- Compact connector assembly rated for 1kg retention force Flexible, slim, fire-rated PVC jacket for easy installation in tight spaces
- Supplied in eco-friendly recyclable, quick-to-open paper packaging with hang tab Individually tested for consistent performance that's 'Connectivity Assured' Designed for economical, high-volume commercial integration projects

- Lifetime warranty for peace of mind



1kgf / 10N (nominal)





Connector Retention Force













Technical Specifications		
Performance		0.5m to 5.0m Lengths
HDMI Certification		High Speed with Ethernet
Supported Data Rate		≥ 6.0Gbpsc, 17.82Gbps agg (4K UHD)
HDMI Clock		CEC, Auto Lip-Sync Correction, Ethernet channel, ARC, eARC, High Dynamic Range (HDR)
Construction		
Conductors		0.5m-3.0m: Solid 32AWG OFC 4.0m-5.0m: Solid 28AWG OFC
Insulation		Polypropylene
Shielding	TMDS Pairs	AL/Mylar, 125% Coverage
	Overall	Al/Mylar, 125% Coverage + Al-Mg Braid 65% Coverage
		AL/Mylar, 125% Coverage + Tinned copper braid, min 85% coverage
Cable Jacket Material		0.5 - 2.0m: VW-1 3.0 - 5.0m UL CMG fire-rated PVC composite materials
HDMI Connector Shell		Premium gauge folded steel, 1μ" Ni-plated
HDMI Connector Pins		Solid OFC, 15μ" 24K Gold plated
Termination		High frequency soldering
HDMI Back-shell		PVC glossy front shell with PVC injection moulded boot and strain relief
Mechanical		
Cable Diameter		0.5m-3.0m: 5.10±0.15mm/0.201in Ø 4.0m-5.0m: 6.50±0.15mm/0.256in Ø
Mounting Depth		0.5m-3.0m: 20.0mm/0.79in Ø 4.0m-5.0m: 22mm/0.87in Ø
Cable Bend Radius		0.5m-3.0m: 25.50mm/1.00in Ø 4.0m-5.0m: 32.50mm/1.28in Ø

Part No	Length	Fire Rating	Master Ctn Qty	Master Ctn Size
K16015-0050-CH	0.5m	VW-1	80	290mm x 264mm x 282mm 11.42in x 10.39in x 11.10in
K16015-0100-CH	1.0m		72	
K16015-0150-CH	1.5m		64	
K16015-0200-CH	2.0m		56	
K16015-0300-CH	3.0m		52	
K1601G-0400-CH	4.0m	UL CMG	42	558mm x 298mm x 240mm 21.97in × 11.73in × 9.45inq
K1601G-0500-CH	5.0m		36	

Kordz products are sold with a limited warranty as outlined at: www.kordz.com
@2025 Kordz International. All rights reserved. Kordz Connectivity.Assured & Kordz range logos are trademarks or registered trademarks of Kordz International in Hong Kong and in other countries. All other trademarks are the property of their respective owners.