



Technical Data Sheet

PRS SlimCat™ Cat6A Network Cable

Makes installation easier

Kordz PRS SlimCat™ Cat6A Network Cable is the industry-leading highly flexible network cable designed for high performance and high-density installations, delivering ANSI/TIA-568.2-D Cat6A permanent link performance up to 50 metres. With a slim 5mm diameter F/UTP form factor and a recommended bend radius of just 40mm, the cable enables wired network connectivity to be delivered in a variety of challenging installation applications and can go where other cables can't. The Kordz PRS SlimCat™ Cat6A Network Cable also offers essential space saving advantages in dense rack installations by halving bundle sizes. This allows better airflow and heat dissipation, which in turn improves equipment reliability, serviceability and performance. Fully compatible with PoE++ at 100W, together with its small cable footprint, Kordz PRS SlimCat™ Network Cable is ideal for easy retrofitting of devices such as Wi-Fi access points and IP CCTV cameras to existing projects. Equally, the cable system comes into its own when non-destructive, discrete cable running techniques are required for use in historic buildings or other challenging retrofit installs. Complete the Kordz PRS SlimCat™ end-to-end system by pairing the cable with the corresponding Kordz PRS SlimCat™ RJ45 Shielded Crimp Connectors and Shielded Keystone RJ45 Sockets to ensure reliable, compact connectivity in your next installation.

- Delivers ANSI/TIA-568.2-D Cat6A permanent link performance up to 50m, ideal for small and medium size installations
- Space-saving F/UTP design, enabling reliable wired networks to the places other systems can't reach
- Reducing bundle sizes by almost half (cross-sectional area)
- IEEE802.3bt 100W PoE++ capable
- Simultaneous UL444 CMG and CPR Dca fire rating for full compliance with US and EU safety requirements
- Conveniently packaged in a Reel-in-Box delivery system that's easy to identify in a van or on-site
- AS/NZS S008:2010 compliant
- RoHS compliant
- Kordz Lifetime Warranty



Technical Specifications							
Construction							
Conductor		28AWG solid OFC 0.338 +0/-0.02mm					
Insulation		Polyethylene, 0.67±0.1 mm					
Twisting		4 twisted pairs of conductors, 2 single conductors paired					
Twisted pair colour code		1: white-blue / blue 2: white-orange / orange 3: white-green / green 4: white-brown / brown					
Shielding		shielded (F/UTP)					
Jacket Material		FRLSZH composite					
Outer diameter		5.0 ± 0.5 mm					
Mechanical							
Minimum Bend Radius	without load	≥ 20.0 mm					
	with load	≥ 40.0 mm					
Temperature Range	During operation	-20 °C to 60°C					
	During installation	0°C to 50°C					
Electrical Properties - at 20°C ± 5°C							
DC resistance		max. 23.6 Ω/100 m at 20°C					
Resistance unbalance		max. 4% at 20°C					
Insulation resistance (500V)		min. 5000 MΩ/km at 20°C					
Mutual capacitance		max. 5.6 nf/100 m at 1 kHz					
Capacitance unbalance (pair to ground)		max. 330 pf/100 m at 1 kHz					
Nominal velocity of propagation		nom. 67%					
Test voltage (DC, 1min)		1 kV / 1 min					
Part No	Color	Gauge	Cable Type	Fire Rating	Spool Length	Packaging Style	Packaging Dimensions
K34202-305M-BK	Black	28AWG	F/UTP	CPR Dca s1,d1,a1 / UL 444 CMG	305m (metre-marked)	Reel-in-Box	330mm x 265mm x 340mm 13.0in x 10.4in x 13.4in
K34202-305M-BL	Blue						
K34202-305M-WH	White						
K34202-305M-GN	Green						
K34202-305M-YL	Yellow						
K34202-305M-PP	Purple						

Kordz products are sold with a limited warranty as outlined at: www.kordz.com
©2024 Kordz International. All rights reserved. Kordz Connectivity.Assured & Kordz range logos are trademarks or registered trademarks of Kordz International in Hong Kong and in other countries.
All other trademarks are the property of their respective owners.